



## Description

Gaska Tape's V700 Series product is a light density closed-cell Polyvinyl Chloride foam. This economical, general-purpose foam tape is manufactured for use in applications requiring positive seals on irregular surfaces or when flex and conformability to seal tight radius curves are

critical considerations.

Characteristics common to all closed-cell vinyl foam products include the ability to make a long life seal against air, moisture, light and dust penetration. Closed-cell vinyl foam completely seals out air, moisture, light and dust when compressed 30% or more.

## Performance Characteristics



- Absorbs shocks, cushions, deadens sound and eliminates excess vibration.
- Provides an excellent buffer between contact surfaces.
- V700 Series is a self-extinguishing formulation and meets FMVSS 302A
- V710 is cast-on a 7 mil clay coated paper.
- V715 is cast-on a 1.5 mil polyester film to provide dimensional stability, and is a self-wound product.
- Die or kiss cutting material is available on 84# polycoated release paper or 12pt. release board.
- V710 is available up to 2" thick as a tri-lamination.

- Light density foam is easy to compress and conformable, it is still strong and resilient.
- Black color standard.
- Other colors available upon request.


▪ **V715 with a tough polyester film reduces wear, prevents any tendency to stick to surfaces, and eliminates the possibility of stretching foam.**

▪ **Available with A3 adhesive, an aggressive acrylic that provides an excellent combination of tack and holding power. Bonds quickly to most surfaces that are kept clean, dry and free from contamination.**


## Industry Applications

- Automotive
- Construction
- H.V.A.C.
- Industrial
- Leisure
- Transportation
- Retail

- **Formulated to meet automotive industry specifications: General Motors 6086M-1A, Ford ESB M3G 102-A, and Chrysler MSAY 511-A, B and C.**
- **Inherently resistant to fire, ultraviolet rays, most chemicals, acids and solvents.**



V710



V715

# V700 Series

Low Density

## Roll Sizes

### Available Thicknesses:

V710 .079" – 1.00" (2.0mm – 25.4mm)

V715 .125" – .500" (3.2mm – 12.7mm)

### Available Widths:

.250" – 57" (6.4mm – 1448mm)

### Available Lengths:

10' – 302' (3M – 92M)

## Benefits & Features

Characteristics common to all Gaska Tape closed-cell vinyl foam products include the ability to make a long life seal against air, moisture, light and dust penetration. They cushion and absorb vibration and shock. They also insulate in thermal, electrical and sound applications.

## Typical Physical Properties\*

Test Method		V700
ASTM D-1667	Density	7
	(lbs./cu.ft.)	112
	(kg/m <sup>3</sup> )	
ASTM D-2240	Hardness (shore 00)	14
ASTM D-1667	Compression Deflection @ 25%	0.8
	kPa	6
ASTM D-1667	Compression Set @ 25%	4
GTP (1)	Water Absorption (% by volume)	1.1
ASTM D-412	Tensile Strength	25
	kPa	173
ASTM D-412	Percent Elongation	150
ASTM C-518	Thermal Conductivity (K factor)	0.27
	(btu-in.)/(hr.sq.ft.) (°F)	
	w/mK	0.039
	Recommended Service Temperature	-40 – 180
	(°F)	-41 – 82
	(°C)	
	Recommended Application Temperature	50 – 110
	(°F)	10 – 45
	(°C)	
	Fungi Resistance	Excellent
	Oxidation Resistance	Excellent
	Weather Resistance	Excellent

### Notes:

The length of the rolls vary depending on the thickness of the material. Gaska Tape offers standard length logs, master logs are double the standard length plus 2' and available upon request for quote.

### (1) Gaska Tape Procedure

Typical performance properties and characteristics are based on samples tested and are not guaranteed for all samples of this product.

Data is intended as a guide only and is presented without guarantees and without assumption of liabilities resultant from the use of information provided. This data is not to be used for specification purposes.

## Warranty

Gaska Tape Inc. warrants its product to be free from defects in material and workmanship for a period of twelve (12) months beginning on the date of purchase, provided the purchaser installs and uses the products according to any instructions provided by Gaska Tape Inc. Any product which fails during the warranty period due to a defect will be replaced.

Upon request, Gaska Tape Inc. will be pleased to provide a copy of its written Limited Warranty with complete details of coverage, conditions and limitations.

Gaska Tape Inc. makes no other warranty, expressed or implied, and specifically disclaims and disavows any implied warranty of merchantability and of fitness for a particular use.

Distributed by:

**Advanced Gasket & Supply, Inc.**

3336 Stuart Drive Fort Worth, TX 76110

Phone: 817.927.0500 Fax: 817.927.0554

[www.advancedgasket.com](http://www.advancedgasket.com)



Rev. 10-05